



FG9213MT 13+13 Litre MELTING GAS FRYER.



- Unit made of steel throughout
- 2mm thick pressed top
- Height-adjustable steel feet
- Steel tanks with rounded corners and pressed bottom for ease of cleaning
- Top with anti-drip edge
- Wide cool zone in the bottom for collecting cooking debris
- Chrome-plated cast brass draining tap for oil drainage in the oil collector (fitted with filter) situated in the base
- Heating elements protected by a pull-out chrome-plated grid
- High thermally efficient nickel-plated cast iron burners (approx.1 kw/l) fitted with electrovalve.
- Bulbs protected for knock resistance;
- The "melting" versions have precision electronic controls that gradually take the fat to the pre-set temperature guaranteeing high performance and productivity.
- The "melting" system provides for:
 - low temperature drop when introducing the load
 - fast temperature recovery
 - more efficient use and longer life of the oil
- Features:
 - 1 basket per tank in case of half module
 - 3 baskets on single module (2 half- and one single basket)
 - 1 oil collector for each appliance

General technical data

Dimensions: (mm)	
800x900x900H	
Volume: (m ³)	1,6
Weight: (Kg)	140
Gas connection	
kW	23
UNI ISO 7\1 R 1/2"	
Electrical connection	
kW	0,2
Power supply voltage	
230V/1 50Hz	

